

## SINGLE AXLE AGRICULTURAL TIPPING TRAILER NSR SERIES

This single axle agricultural trailer is equipped with a three-way tipping and a rear tilting mechanism. It is especially designed to transport loose goods.

**Chassis:** The chassis is made up of two U-section (UPN) longitudinal members, which are held together by 4 electro-welded U-section (UPN) crossmembers.

**Body:** The platform is made of checker plate and is equipped with sideboards. The up- and downward-opening tailgate is supplied as standard equipment, except on types NSR 15/20. Sideboards are in one piece, except for types NSR 90/100, whose sideboards are divided in two by a center post.

The body's robust structure is made up of two U-section (UPN) longitudinal members which are held together by U-section and rectangular hollow section stiffening crossmembers, except for types NSR 30 T/P, NSR 40 T/P e NSR 50 T/P, which have C-section longitudinal members made of press-formed sheet.

**Braking:** mechanical braking, hydraulic and semi-continuous braking or pneumatic, semi-continuous and automatic braking (see table below).

**Suspensions:** stiff.

**Painting:** anti rust primer and two coats of synthetic paint.

### types

Code	Type	Body Dimensions [m]	Technically permissible load [kg.]	Maximum authorised load (In Italy) [kg.]	Empty weight [kg.]	Braking	Platform height from the ground {·} [m]	Tilting	Single wheels
00022.R	<b>NSR 15 P</b>	2.20x1.50x0.40	2000	1500	500	mechanical	0.74	rear	205/70 R 15 retread
00052.R	<b>NSR 15 T</b>	2.20x1.50x0.40	2000	1500	535	mechanical	0.74	three-way	205/70 R 15 retread
00023.R	<b>NSR 20 P</b>	2.20x1.50x0.40	2000	2000	500	mechanical	0.74	rear	205/70 R 15 retread
00053.R	<b>NSR 20 T</b>	2.20x1.50x0.40	2000	2000	535	mechanical	0.74	three-way	205/70 R 15 retread
00024.R	<b>NSR 40 P</b>	2.70x1.70x0.40	3500	3500	810	mechanical	0.83	rear	10.0/75 - 15.3 10 P.R.
00057.R	<b>NSR 30 T</b>	2.70x1.70x0.40	3500	2500	840	mechanical	0.83	three-way	10.0/75 - 15.3 10 P.R.
00058.R	<b>NSR 40 T</b>	2.70x1.70x0.40	3500	3500	840	mechanical	0.83	three-way	10.0/75 - 15.3 10 P.R. new
00026.R	<b>NSR 50 P</b>	3.00x1.80x0.50	4500	4500	960	mechanical	0.85	rear	10.0/75 - 15.3 18 P.R. new
00062.R	<b>NSR 50 T</b>	3.00x1.80x0.50	4500	4500	960	mechanical	0.85	three-way	10.0/75 - 15.3 18 P.R. new
00028.R	<b>NSR 60 P</b>	3.50x2.00x0.50	6000	5000	1280	mechanical	0.97	rear	265/70R19.5 used
00066.R	<b>NSR 60 T</b>	3.50x2.00x0.50	6000	5000	1280	mechanical	0.97	three-way	265/70R19.5 used
00030.R	<b>NSR 70 P</b>	4.00x2.20x0.60	8000	5000	1600	mechanical	1.04	rear	305/70 19.5 retread
00068.R	<b>NSR 70 T</b>	4.00x2.20x0.60	8000	5000	1660	mechanical	1.04	three-way	305/70 19.5 retread
00032.R	<b>NSR 80 P</b>	4.00x2.20x0.60	8000	6000	1600	hydraulic and semi-continuous	1.04	rear	305/70 19.5 retread
00033.R	<b>NSR 80 P P</b>	4.00x2.20x0.60	8000	6000	1600	pneumatic, semi-continuous and automatic	1.04	rear	305/70 19.5 retread
00070.R	<b>NSR 80 T</b>	4.00x2.20x0.60	8000	6000	1660	hydraulic and semi-continuous	1.04	three-way	305/70 19.5 retread
00071.R	<b>NSR 80 T P</b>	4.00x2.20x0.60	8000	6000	1660	pneumatic, semi-continuous and automatic	1.04	three-way	305/70 19.5 retread
00034.R	<b>NSR 90 P</b>	4.60x2.40x0.60	10000	5000	1910	mechanical	1.08	rear	305/70 19.5 retread
00072.R	<b>NSR 90 T</b>	4.60x2.40x0.60	10000	5000	1910	mechanical	1.08	three-way	305/70 19.5 retread
00036.R	<b>NSR 100 P</b>	4.60x2.40x0.60	10000	6000	1900	hydraulic and semi-continuous	1.08	rear	305/70 19.5 retread
00037.R	<b>NSR 100 P P</b>	4.60x2.40x0.60	10000	6000	1900	pneumatic, semi-continuous and automatic	1.08	rear	305/70 19.5 retread
00074.R	<b>NSR 100 T</b>	4.60x2.40x0.60	10000	6000	1960	hydraulic and semi-continuous	1.08	three-way	305/70 19.5 retread
00075.R	<b>NSR 100 T P</b>	4.60x2.40x0.60	10000	6000	1960	pneumatic, semi-continuous and automatic	1.08	three-way	305/70 19.5 retread

{·} Platform height is measured with standard tires.

## optional equipment

Optional equipment upon request	
Code	Description
00262.A	Side panel extensions H=0.40 m for NSR 40 T/P
00263.A	Side panel extensions H=0.50 m for NSR 50 T/P
00264.A	Side panel extensions H=0.50 m for NSR 60 T/P
00266.A	Side panel extensions H=0.60 m for NSR 70 T/P e NSR 80 T/P
00267.A	Side panel extensions H=0.60 m for NSR 90 T/P e NSR 100 T/P
00268.A1	Up- and downward-opening sideboards for NSR 40 T - NSR 50 T - NSR 40 T M - NSR 50 T M
00268.A2	Up- and downward-opening sideboards for NSR 60 T - NSR 70 T - NSR 80 T - MU 80 - NSR 60 T M - NSR 70 T M - NSR 80 T M
00268.A3	Up- and downward-opening sideboards for NSR 90 T - NSR 100 T - MU 90 - MU 140 - MU 140 P
00270.A	Grain chute
00279.A	Additional charge for new 10.0/75 – 15.3 14 P.R. single tires for NSR 40 T/P
00282.A1	Hydraulic braking with drum 300x60 (internal reference only) for NSR 40 T/P
00282.A2	Hydraulic braking with drum 300x60 (internal reference only) for NSR 50 T/P
00282.A3	Hydraulic braking with drum 300x60 (internal reference only) for NSR 60 T/P
00282.A4	Hydraulic braking with drum 300x60 (internal reference only) for NSR 70 T/P
00282.A5	Hydraulic braking with drum 300x60 (internal reference only) for NSR 90 T/P
00283.A1	Automatic hydraulic braking, for NSR 80 T/P
00283.A2	Automatic hydraulic braking, for NSR 100 T/P
00284.A1	Protection frame for bale transport on TL 15-20 - NSR 15 T/P -20 T/P H= 1.00 m
00284.A2	Protection frame for bale transport on TL 25-30-35 - NSR 40 T/P- NSR 40 T/P M H= 1.10 m
00284.A3	Protection frame for bale transport on NSR 50 T/P - NSR 50 T/P M H= 1.10 m
00284.A4	Protection frame for bale transport on NSR 60 T/P- NSR 60 T/P M H= 1.20 m
00284.A5	Protection frame for bale transport on NSR 70 T/P - 80 T/P- NSR 70 T/P M H= 1.40 m
00284.A6	Protection frame for bale transport on NSR 90 T/P - 100 T/P H= 1.40 m
00286.A	Additional winch
00287.A	Additional charge for new 215/75 R 17.5 dual tires on NSR 70 T/P –NSR 80 T/P – NSR 90 T/P – NSR 100 T/P
00289.A	Additional charge for new 265/70 R 19.5 tires for NSR 60 T/P
00297.A	Additional charge for retread 285/70 R 19.5 tires for NSR 60 T/P
00328.A	Width extensions to 2,45 / 2,55 m internal width for NSR 90/100 (for internal reference only) Note: When width extensions are used, you can only apply one set of side panels (no height extensions).
00332.A	Hydraulic jack for NSR/60/70/80/90/100
The side panel extensions must be ordered together with the trailer, because center posts and hinges are not supplied if no side panel extensions are ordered. Tyres: see art. 7 of the general terms and conditions for sale and use	

*The trailers main characteristics, as above indicated, could be modified at any time and without notices from Ferruzzi Co. in order to offer to the customers a product with increased quality and performance.*